

VR series

- Low ESR, High reliability 低等效串联电阻, 高可靠性
- Load life of 8000 hours at 125°C 直流负载寿命 125°C-8000 小时
- Compliant to the RoHS2.0 directive 符合 RoHS2.0 规范



Specifications 系列参数

Items 项目	Characteristics 特性	
Rated Voltage Range 额定电压范围	16V ~ 63V DC	
Capacitance Range 容量范围	39 ~ 820μF	
Capacitance Tolerance 容量偏差	M : ±20%	
Operating Temp. Range 工作温度范围	-55°C ~ +125°C	
Dissipation Factor 损耗角正切	Not to exceed the value specified 不超过规格值	
Leakage Current 漏电流	Not to exceed the value specified (after 2 minutes) 不超过规格值 (充电 2 分钟后测试)	
ESR (100K~300KHz) 等效串联电阻	Not to exceed the value specified 不超过规格值	
Endurance 125°C, 8000h, Rated voltage applied 寿命: 125°C 加载额定电压连续工作 8000 小时	Capacitance Change 容量变化	Within ±20% of the value before test 初始值±20%以内
	Dissipation Factor 损耗角正切	Not to exceed 150% of the value specified 不超过 1.5 倍规格值
	ESR 等效串联电阻	Not to exceed 150% of the value specified 不超过 1.5 倍规格值
	Leakage current 漏电流	Not to exceed the value specified 不超过规格值
Moisture Resistance 85°C, RH85%, 1000h, Rated voltage applied 耐湿性 85°C, RH85% 加载额定电压连续工作 1000 小时	Capacitance Change 容量变化	Within ±20% of the value before test 初始值±20%以内
	Dissipation Factor 损耗角正切	Not to exceed 150% of the value specified 不超过 1.5 倍规格值
	ESR 等效串联电阻	Not to exceed 150% of the value specified 不超过 1.5 倍规格值
	Leakage Current 漏电流	Not to exceed the value specified 不超过规格值
Resistance to Soldering Heat After the recommended soldering conditions 耐焊接热 推荐焊接条件处理后测试	Capacitance Change 容量变化	Within ±5% of the value before test 初始值±5%以内
	Dissipation Factor 损耗角正切	Not to exceed the value specified 不超过规格值
	ESR 等效串联电阻	Not to exceed the value specified 不超过规格值
	Leakage Current 漏电流	Not to exceed the value specified 不超过规格值 (Charging treatment 充电处理)

※ When there is any doubt, measure after charging treatment below.

Charging treatment: at 125 °C, Rated voltage is loaded for 60 minutes continuously.

如有疑问, 请进行充电处理后再测试, 测试条件: 在 125°C 环境温度下连续施加额定直流电压 60 分钟。

Dimensions 尺寸(Unit单位:mm)

	ΦD	L	W	H	C	P	R	T ₁ , T ₂
	8	12.2	8.3	8.3	9.0	3.2	0.8~1.1	0.2max.
	10	10.5	10.3	10.3	11.0	4.6	0.8~1.1	0.2max.
	10	12.8	10.3	10.3	11.0	4.6	0.8~1.1	0.2max.

Capacitance List 容量对照表

W.V (S.V) SIZE	16 (18)	25 (29)	35 (40)	50 (58)	63 (72)
8×12.2	330 ~ 560 μ F	150 ~ 330 μ F	100 ~ 220 μ F	56 ~ 82 μ F	39 ~ 68 μ F
10×10.5	330 ~ 560 μ F	180 ~ 330 μ F	150 ~ 270 μ F	68 ~ 120 μ F	47 ~ 82 μ F
10×12.8	470 ~ 820 μ F	220 ~ 470 μ F	180 ~ 330 μ F	82 ~ 150 μ F	68 ~ 120 μ F

Characteristics List 规格特性表

W.V. 工作电压 (V)	Capacitance 容量 (μ F)	L.C. 漏电流 (μ A, 2min)	tg δ 损耗角正切 (120Hz, 20°C)	ESR 等效串联电阻 (m Ω , 100kHz)	Rated Ripple Current 额定纹波电流 (mA, r.m.s)		Size 尺寸 Φ D×L (mm)	Part Number 物料编码
					105°C < T _x ≤ 125°C	T _x < 105°C		
16	470	1000	0.10	15	980	2500	8×12.2	PVR471M016F1CTR□□□
	560	1000	0.10	15	1000	2500	10×10.5	PVR561M016G1ETR□□□
	820	1000	0.10	12	1220	3100	10×12.8	PVR821M016G1DTR□□□
25	330	1000	0.10	18	940	2400	8×12.2	PVR331M025F1CTR□□□
	330	1000	0.10	18	960	2450	10×10.5	PVR331M025G1ETR□□□
	470	1000	0.10	15	1150	2950	10×12.8	PVR471M025G1DTR□□□
35	220	1000	0.10	22	890	2200	8×12.2	PVR221M035F1CTR□□□
	270	1000	0.10	22	900	2300	10×10.5	PVR271M035G1ETR□□□
	330	1000	0.10	18	1090	2800	10×12.8	PVR331M035G1DTR□□□
50	82	820	0.10	25	810	2100	8×12.2	PVR820M050F1CTR□□□
	100	1000	0.10	25	830	2200	10×10.5	PVR101M050G1ETR□□□
	150	1000	0.10	20	1010	2600	10×12.8	PVR151M050G1DTR□□□
63	56	705	0.10	25	800	2050	8×12.2	PVR560M063F1CTR□□□
	82	1000	0.10	25	810	2000	10×10.5	PVR820M063G1ETR□□□
	100	1000	0.10	20	1000	2560	10×12.8	PVR101M063G1DTR□□□

* For the last 4 digits of the part number, please refer to the part number system on page 178.

物料编码的最后 4 位，请参考 178 页物料编码系统。

Frequency Coefficient for Ripple Current 纹波电流频率系数

Frequency 频率	120Hz≤freq.<1KHz	1KHz≤freq.<10KHz	10KHz≤freq.<50KHz	50KHz≤freq.<100KHz	100KHz≤freq.<500KHz
Coefficient 系数 (C≤47 μ F)	0.05	0.25	0.55	0.80	1.00
Coefficient 系数 (C>47 μ F)	0.05	0.30	0.70	0.85	1.00